
JUKI®

1-needle, Embroidering Sewing Machine

LZ-271



The color of the JUKI LZ-271 embroidering machine has been changed to a modern, bright urban white, thereby realizing a fresh appearance.
It is capable of running at a sewing speed of 2,000 rpm with a consistent sewing performance.
The zigzag width can be as large as 12mm.
Highly durable components are used as the machines major parts, thereby realizing smooth running at high speed with minimal machine vibration. This sewing machine is highly evaluated by the embroidering industry.




LZ-271

FEATURES

1. **Beautifully finished seams and a wide range of applications.**
   This machine can be used for extra light-weight materials including lawn and organdy, medium-weight materials including those used for blouses and handkerchieves, and heavy-weight materials on which names and labels are to be embroidered. Beautifully finished seams free from needle swaying or material breakage are assured every time.

2. **The zigzag width can be as large as 12 mm.**
   The zigzag width is regulated up to 12 mm using the knee lifter. This knee lifter has been designed to fit the jut-type knee lifter widely used by zigzag stitch machines.


3. **Consistent, fine-quality seams.**
   Highly durable and reliable components are used as its major parts, including the needle bar oscillating mechanism, thereby leading to smooth running without vibration even at high speed, the result of which is consistent, high-quality seams.







Using the jut-type knee lifter with the zigzag width pointer released



SPECIFICATIONS

Applications	Embroidering on light-, medium- and heavy-weight materials
Sewing speed	Max. 2,000 rpm (with a zigzag width is as large as 10 mm) Normal 1,700 rpm (with a zigzag width is as large as 12 mm)
Needlebar stroke	33.4 mm
Needle	DB x 1 #9 through #18 (standard : #11)
Zigzag width	0 ~ 12mm
Zigzag width regulating method	Using the jut-type knee lifter with the zigzag width pointer released.
Hook	DB-type hook for embroidering
Lubrication method	Centralized lubrication (using an oiler)
Material handling area on the machine	270 mm (from the needle entry to the bottom of the arm)

Installing the attachments (optional)

A compass and cord embroidering attachment can be installed on the machine.
The compass (asm.) (B3352-271-0A0) and scallop (asm.) (B5001-271-0A0) can be ordered from us as options.

● To order, contact your nearest JUKI distributors.

(Note) The color of the product shown in photographs in this catalog is slightly different from the actual color of the product.

JUKI®

JUKI CORPORATION

INTERNATIONAL SALES DIVISION
8-2-1, KOKURYO-CHO,
CHOFU-SHI, TOKYO 182-8655,
JAPAN
PHONE : 03(3430)4001~5
FAX : 03(3430)4909.4914.4984
TELEX : J22967
http://www.juki.co.jp

* Specifications and appearance are subject to change without prior notice for improvement.
Read the instruction manual before putting the machine into service to ensure safety.
The description this catalog is as of July, 1998.

JULY,1998 Printed in Japan(T)